

Polarization maintaining fiber (PMF)

PM13G-80

Oelabs polarization maintaining fiber (PMF) is specially designed for fiber optical gyroscopes (FOGs) and polarization-sensitive components applications. This kind of fiber exhibits extremely low attenuation and excellent birefringence characteristics, and uses in a variety of demanding applications.

Application

- ❖ Fiber optical gyroscopes (FOGs)
- ❖ Polarization maintaining fused- fiber couplers
- ❖ Polarization-sensitive components
- ❖ High performance transmission lasers pigtails
- ❖ Polarization- based sensors.

Characteristics

- ❖ Short beat length
- ❖ Extremely high birefringence
- ❖ Excellent polarization maintaining properties
- ❖ Tight geometric tolerances and very low attenuation
- ❖ Low bending-induced attenuation
- ❖ Tight tolerance, dual-layer, and UV-Acrylate coating
- ❖ High environmental stability and reliability



Specification

Parameter	Unit	Specification	
Fiber Type		PM13G-80-U16	PM13G-80-U13
Optical Properties			
Operating Wavelength	nm	1310	
Cut-off Wavelength	nm	1100 - 1290	
Mode Field Diameter	μm	6.0 ± 1.0 @1310nm	
Attenuation	dB/km	≤ 0.6@1310nm	
Beat Length	mm	≤ 3.0@1310nm	
Typical Crosstalk	dB/km	≤ -22 @1310nm	
Geometric Properties			
Cladding Diameter	μm	80.0 ± 1.0	
Coating Type	--	Dual-layer; UV-Acrylate	
Coating Diameter	μm	170 ± 5	135 ± 3
Cladding non-circularity	%	≤ 2.0	
Core/Cladding Offset	μm	≤ 1.0	
Environmental and Mechanical			
Operating temperature range	°C	- 45 to + 85 °C	
Proof test level (standard)	kpsi	100	